

# Product Information



## METCON MCC 5109 METCON TOUGH COAT PRIMER

### ➤ PRODUCT DESCRIPTION

Metcon MCC 5109 is water thinnable primer based on alkali resistant emulsion. It has good penetration on cement surfaces. Its film gives long lasting water resistance.

### ➤ RECOMMENDED USAGE

As a primer MCC 5109 may be used on any old or new cement plaster, cement concrete, GRS etc.

### ➤ DIRECTIONS FOR USE

The material is to be stirred well before use. It may be diluted with water maximum 30%. It can be applied by brush or roller or spray. If the substrate is highly absorbent one additional coat may be required.

### ➤ TECHNICAL SPECIFICATIONS

1. TYPE	Alkali resistant emulsion
2. SHADE	White
3. VOLUME SOLIDS	35 ± 5%
4. GLOSS	Matt
5. THINNER INTAKE	1. – 40% (by wt)
6. pH	8 – 8.5
7. THEORETICAL COVERAGE	10 – 12 sq.mtr/litre per coat
8. DRYING TIME	Surface Dry : 20 – 30 minutes
9. APPLICATION BY	Brush or Roller
10. RECOATABILITY	After 4 – 6 hrs
11. PACKING	20 kg Pail
12. STORAGE	One year in sealed container
13. SAFETY PRECAUTIONS	Since the paint is based on water thinnable ingredients there is no risk of fire. Avoid breathing or inhaling mist. In case of spillage on the skin, it should be immediately washed with plenty of water & seek medical aid.

The information contained above is given in good faith but without warranty as the method and conditions of use of our products are beyond our control. For further details on application and precautions please contact:

**METCON COATINGS & CHEMICALS (INDIA) PVT. LTD.**

ISO 9001 : 2008 Certified

Works & Admn. Office : Plot No. C-310, Pawne Village, TTC MIDC Area,  
Pawne, Navi Mumbai-400 705. Maharashtra (India)  
Tel.: 91 (22) 41412424 (100 lines)  
E-mail: info@metconcoatings.com Website: www.metconcoatings.com